SLUNLI

NO FOREIGN DISSEM/NO DISSEM ABROAD/ CONTROLLED DISSEM/BACKGROUND USE ONLY

Table 6

RADIATION INTENSITY OVER THE WAKE OF A RADIO-ACTIVE CLOUD

						R.	ADIA'	ricn	11/11	ensi: Af	TY OF	VER AGR	THE W	AKE (of a T. •	RADIO-	ACTIVE	; CLOUD			coefficients
Distance from the centre of burst	Radiation intensity on the axis of the wake after a burst of the following yield in kilotons:															requir	Equivalent distances, and the coefficients required for the evaluation of radiation intensity not on the axis of the wake, at the following distances from the axis (in Kms.):				
	2	3	5	10	15	20	30	40	50	75	100	150	200	300	500	700	1000	2	5	10	20
2	100	70	145	25	20	15	10	8	6	5	4	3	2.5	5	1.5	1.2	1	-	-	-	
3	70	100	75	40	30	PS	20	10	12	40	В	6	4	3	2	1.B	1.5	-	•	•	•
4	30	50	100	60	45	40	30	25	20	15	10	8	6	5	3	2.5	2	140 (0.€)	-	-	
6	15	25	40	100	75	60	45	35	30	20	15	12	10	8	5	4	3	30 (n.6)	150 (0.2)	-	
В	6	10	20	50	80	70	60	45	40	30	25	20	15	10	8	6	. 5	25 (0.6)	100 (0.3)	-	-
10	4	6	12	30	50	80	75	60	55	140	30	25	20	12	10	8	c	25 (0.6)	100 (0.3)	-	-
12	2	4	7	20	30	60	80	75	70	50	40	30	25	15	12	10	7	25 (0.6)	90 (0.3)	-	-
14	1.6	2.5	6	15	25	35	50	80	75	55	45	32	28	18	15	12	8	25 (0.6)	70 (0.3)	-	• (1)
16	1.2	2	4	10	15	25	40	50	80	65	55	40	35	25	18	15	10	25 (0.6)	70 (0.3)	250 (0.05)	-
20	0,8	1.2	2.5	. 6	10	15	25	30	45	75	60	50	40	30	20	18	12	30 (0.7)	70 (0.3)	200 (0.1)	-
25	0.5	0.8	1.5	4	6	9	15	20	30	45	70	65	50	40	30	20	15	30 (0.8)	60 (0.4)	175 (0.15)	500 (0.05)
30	0.3	0.5	1	2.5	4	6	10	15	20	30	40	70	60	50	35	30	20	30 (0,9)	60 (0.4)	150 (0.15)	500 (0.05)
40	0,2	0.3	0.5	1.2	2	3	5	7	10	20	25	40	70	55	50	140	30	1,0 (0,9)	60 (0.5)	125 (0,2)	400 (0.05)
50	0,1	0.2	0.3	0.7	1.2	2	3	4	5	٥	12	20	30	70	55	50	40	40 (0.9)	70 (0.5)	125 (0.3)	300 (0.05)
60		0.1	0.2	0.5	0.8	1.2	2	3	4	6	9	15	20	35	70	65	.50	70 (1)	80 (0.7)	125 (0.4)	300 (0.1)
70	-	_	0.1	0.3	0.5	0.8	1.5	2	2.5	4	6	10	15	25	50	7 0	60	70 (1)	80 (0.7)	125 (0.4)	300 (0.1)
80	_	-	-	0.2	0.4	0.6	1	1.2	2	3	5	7	10	18	35	50	70	80	90	125	250
90	-	_	-	0,1	0.3	0.5	0.8	1	1.5	2.5	3.5	5	8	15	25	40	60	90	100	125	250
100	-	-	-	-	0.2	0.4	0.6	0.8	1	2	3	14	6	10	20	30	50	100	100	125	250
125	-	-	-	-	0.1	0, 2	0.4	0.5	0.7	1	1.2	2.5	4	6	12	20	30	125	125	150	250
150		-	-	-		0.1	0.2	n. 3	0.5	0.7	1	3	2.5	14	8	12	20	150	150	175	250
175	-	-	-	-	, -	-	0.1	0.2	0,3	0.5	0.7	1	1.5	3	6	8	15	175	175	200	250
200	-	-	-	-	-	-	-	0,1	0, 2	0.4	0.6	0.8	1.2	2	4	6	10	200	200	200	250
250	-	-	-	-	-	-	-	-	0,1	0.2	0.3	0.6	0.8	1.2	2.5	4	6	250	250	250	300
300	-	-	-	-	-	-	-	-	-	0.1	0.2	0.3	0.5	0.9	1.5	2.5	4	300	300	300	400
400	-	-	-	-	-	-	-	-	-	-	0.1	0.2	0.3	0.5	0.8	1.2	2	400	400	400	400
500	-	-	-	-	-	-	-	-	-	-	-	0.1	0.2	0.3	0.5	0.8	1.5	500	500	500	500

Thid. Methods of evaluating the radiation position when concentrated use is made of nuclear weapons, and some problems connected with the protection of troops operating in contaminated area. Voyeniziat. Moscow. 1960.

/Remark:



NO FOREIGN DISSEM/NO DISSEM ABROAD/ CONTROLLED DISSEM/BACKGROUND USE ONLY